

CPI OLD WORLD WB STAINS

Properties

- Type: non-acid, polymer-bonded concrete stain
- Color: Various (see color samples chart)
- Odor: Slightly pungent
- Toxicity: Low-Harmful if swallowed
- Flammability: Non-flammable
- VOC's: very low
- Composition: Various UV-stable coloring agents in an aqueous penetrating polymer binder

Coverage

- 150-400 ft²/gal

Environmental Impact

- Contains no arsenic
- Contains no lead
- Contains no mercury
- Conforms to all VOC regulations

Product Description:

CPI OLD WORLD WB STAINS are a line of water and polymer based stains that penetrate into concrete surfaces to produce vibrant, long-lasting colors that enhance any concrete surface.

CPI OLD WORLD WB STAINS may be applied to any clean, properly prepped concrete or concrete overlay surface.

Application Instructions:

Preparation

- Bring CPI OLD WORLD WB STAIN to room temperature.
- Clean and prepare the surface thoroughly using CPI SUPER PREP diluted 1:1 with water.
- Rinse the floor well, until there is no residue or suds remaining.
- Mop floor with a neutral pH no rinse floor cleaner.
- Allow floor to dry completely before applying CPI OLD WORLD WB STAIN
- Sample test CPI OLD WORLD WB STAIN in an inconspicuous area.

Application

- DO NOT DILUTE CPI OLD WORLD WB STAIN. Shake container well. Product tends to settle. For best consistency in color, shake well, pour half gallon into another container, shake remaining half gallon well to stir up pigment in bottom of jug, mix back into first half gallon. Check original container to make sure no pigment remains in bottom of jug. If pigment remains, pour some of the stain back into jug and shake well to mix it.
- Apply stain with a Plastic Pump Up Sprayer, Brush or Sea Sponge, according to your desired outcome
- Faux finish looks are possible; for a softly variegated look, apply in thin, random layers
- Do not over apply: surface should be saturated and slight puddling is okay depending on the look you want to achieve.
- If you are doing multiple layers of stain make sure that you allow stain to dry in between coats, 30 minutes to an 1 hr should be okay but it is still recommended to check to make sure no spots are still wet and you are not leaving footprints before you begin. Wearing shoe covers or socks only is recommended at this point so you will not damage the last layer of stain since it has not had time to fully dry.
- Once you are happy with the color, allow surface to dry completely (6-8 hrs). Drying time will vary according to surface conditions and humidity.

NOTE: Due to variations in concrete composition, age, surface conditions, surface preparation and application techniques, exact color of each stain will vary from project to project.

Sealing:

CPI OLD WORLD WB STAIN MUST BE SEALED. Seal surface with CPI OLD WORLD SEALER or CPI EPOXY 510 WB or CPI QUICK DRY EPOXY 310 - SOLVENT-ACRYLIC SEALERS ARE NOT RECOMMENDED WITH THIS PRODUCT. IF USING POLYURETHANE, PRIME WITH WATER-BASED EPOXY (510) FIRST OR ALLOW OLD WORLD WB STAIN TO FULLY DRY AT LEAST 18 - 24 HOURS BEFORE APPLYING YOUR POLYURETHANE.

Notice to buyer: disclaimer of warranties and limitations on our liability

This product is intended for use by trained professionals, experienced and trained in the use of these products. We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. No warranty is made, expressed or implied, regarding such other information, the data on which it is based, or the results you will obtain from its use. NO warranty is made, expressed or implied, that our product shall be merchantable or that our product shall be fit for any particular purpose. No warranty is made that the use of such information or our product will not infringe upon any patent. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may cause serious physical injury. Before using, read the material safety data sheet and follow all precautions to prevent bodily harm.

COPYRIGHT CONCRETE PERCEPTIONS, INC 9/11/12