

Perma-Tique

Perma-Tique Antiquing Agent can be applied to interior or exterior newly hardened stamped concrete, unsealed existing stamped concrete, and unsealed existing stamped overlays. Perma-Tique adds color, depth and added visual interest to the textured surface.

*Perma-Tique Antiquing Agent is designed for use on stamped texture surfaces only and should not be used on un-textured or broom finished concrete.

*Perma-Tique is not designed to be a solid color pigment

Product Description:

Perma-Tique Antiquing Agent is a proprietary blend of powders that can be mixed with water to add color and visual interest to stamped concrete surfaces.

Packaging:

Plastic pail containing 3lbs of powder.

Coverage:

1,000- 3,000 per 3lbs of powder. Coverage is only an estimation, depending on mixing rates and overall color required, individual coverage may vary.

Preparation:

When applying over recently poured concrete, it is recommended to clean with Super Prep and rinse with a neutral cleaner to prepare your surface. Make sure that the concrete has gained sufficient strength so that the washing does not damage the surface. The surface must be free of grease, oil residue, curing or sealing compound residue, and any other potential bond breakers.

Mixing and Application:

Add 1/3 cup of Perma-Tique per gallon of clean potable water in a plastic container large enough to allow adequate mixing. Mix vigorously with drill and mixing paddle until all the powder has been incorporated into the water. Use a small container to dip and pour color wash over your surface allowing it to puddle as needed for color concentration. Another method is to pour mixture into a garden style watering can to distribute your mix onto the surface you want to antique. Do not use a broom or brush to manipulate the color as this technique may cause streaks in the color. Periodically remix the Perma-Tique solution as the pigment will settle quickly. Once the surface has been coated, the solids in the Perma-Tique Antiquing Agent will settle and concentrate in the low areas, giving a natural accent color to the textured surface.

*The amount of Perma-Tique added to water can be increased or decreased depending on the amount of antiquing that you desire. The maximum amount recommended is 1 cup per gallon of water.

Sealing: Perma-Tique Antiquing Release must be sealed to maintain longevity. Allow color to dry thoroughly before sealing.

Notice to buyer: disclaimer of warranties and limitations on our liability

This product is intended for use by trained professionals, experienced and trained in the use of these products. We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. No warranty is made, expressed or implied, regarding such other information, the data on which it is based, or the results you will obtain from its use. NO warranty is made, expressed or implied, that our product shall be merchantable or that our product shall be fit for any particular purpose. No warranty is made that the use of such information or our product will not infringe upon any patent. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may cause serious physical injury. Before using, read the material safety data sheet and follow all precautions to prevent bodily harm.

COPYRIGHT CONCRETE PERCEPTIONS, INC 9/11/12