

### CPI OLD WORLD WB SEALER

**Properties:**

Type: water dispersed acrylic polymer coating

Color: colorless

Odor: Slight

Toxicity: non-toxic

VOC's: less than 100gm/L

Flammability: non-flammable

Composition: Acrylic copolymer emulsion

Packaging: 1 gallon

\*CPI recommends this product for indoor use only, outdoor use may require extra care and maintenance.

**Product description:**

CPI Old World WB Sealer is a tough non-yellowing acrylic sealer used to seal and protect stained floors.

\*CPI recommends using this sealer with our CPI Old World WB Stain.

**Shelf Life:**

1 year, when stored in original, unopened container, in dry storage between 60°-80°F.

**Coverage:**

Approximate coverage is 400-500 square feet per gallon, per coat.

\*Coverage rates vary with surface texture and porosity, ambient and surface temperature, and method of application.

**Temperature:**

Best results are obtained when product is applied at substrate temperatures between 40°-90°F. Do not apply when temperatures are above or below these optimal limits or when such temperatures are expected within 12hrs following application. Control interior environment to prevent condensation from forming on the surface prior to sealing or before the sealer has become tack-free.

**Dry Times:**

At 70°F, approximate dry times

Tack Free: 1 hour

Vehicle traffic: 24 hours - 48 hours

**How to use:**

Do not dilute or mix with any other liquid or chemical. Bring product to room temperature. After the OLD WORLD WB STAIN has dried completely and your floor is dust and lint free, apply OLD WORLD WB SEALER in three to four thin uniform coats using a microfiber mop or a non-shedding roller. Do not allow the sealer to puddle. Thicker applications may lead to discoloration and diminished sealer performance. Allow each coat to dry for at least one hour (sealer should be tack free) before applying each additional coat. Once all coats have been applied allow product to dry for several hours or overnight before walking on your floor. Drying times will vary depending upon wet film thickness, surface texture and porosity, ambient and surface temperatures, and humidity.

**Maintenance:**

Periodically inspect surfaces for wear or damage. All concrete sealers will eventually exhibit the effects of wear and traffic. For maximum coating life and performance, wipe up all chemical solvent or petroleum spills as soon as possible. Remove abrasive debris by sweeping or vacuuming. Periodic washing with a pH 7 (neutral) cleaner will help maintain surface luster. Do not use solvent or acid based cleaning materials for general cleaning. Do not use cleaners such as Pine Sol, Bleach or Swiffer Wet Jet. Steam mops should never be used on stained and sealed concrete as they may cause moisture to be trapped in the sealer and cause damage.

\*CPI recommends applying several coats CPI EZ Finish wax as a renewable wear surface to help add an extra layer of protect for your stained and sealed surface.

**NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND  
LIMITATIONS ON OUR LIABILITY**

*This product is intended for use by trained professionals, experienced and trained in the use of these products. We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT.** We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may **CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET AND FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.***

COPYRIGHT 9/11/12 CPI