

SMOOTH FINISH

SMOOTH FINISH acts as a sacrificial acrylic wax coating to help protect and maintain your stain and sealer from damage and wear over time. SMOOTH FINISH will improve the appearance and decrease the overall maintenance cost of most types of sealed concrete floors and countertops.

**Not intended as a stand alone sealer*

**Indoor use only*

Properties

- Type: Super acrylic floor polish
- Color: Clear, non-yellowing
- Odor: Very Mild
- Toxicity: Non-toxic
- Flammability: Non-Flammable
- Composition: Acrylic polymer emulsion, ethylene copolymers, proprietary additives and quality control agents.

Product Description:

SMOOTH FINISH is a high gloss, non-yellowing acrylic polish for use on most types of sealed concrete floors and countertops.

Coverage:

Average coverage is approximately 1,200 square foot; certain floor finishes and may take more or less.

Application Instructions

FLOORS:

Do not dilute wax. Spread SMOOTH FINISH in a thin even coat over the floor using a microfiber or rayon blend mop. Do not let wax puddle when applying, these spots may not dry properly and may remain opaque in color. Allow each coat to dry completely for about 25 to 30 minutes before applying the next coat. Apply each coat in this manner until desired coatings and thickness is reached.

- CPI recommends for first time wax application to apply no less than 6 thin coats, allowing each to dry before beginning the next coat. It is recommended to test the wax before walking on it.
- For re-coating of wax, clean floors thoroughly with a neutral cleaner and allow to dry before beginning the waxing process. If wax is still in good condition only 1 to 2 coats are necessary.
- Use care on freshly waxed floor as scratching is still possible. Once the last wax coat has been applied allow to completely dry for 24 for foot traffic and 72 hours for regular use.

COUNTERTOPS:

Do not dilute wax. Using a spray bottle, apply wax to countertops and wipe with a microfiber rag. Apply 2 to 3 coats allowing each coat to dry for about 25 to 30 minutes. To keep countertops looking new and glossy reapply when shine becomes dull or scratches appear.

Maintenance

Periodically inspect surfaces for wear or damage. All concrete sealers will eventually exhibit the effects of wear and traffic. For maximum coating life and performance, wipe up all chemical solvent or petroleum spills as soon as possible. Remove abrasive debris by sweeping or vacuuming. Periodic washing with a pH 7 (neutral) cleaner will help maintain surface luster. Do not use solvent or acid based cleaning materials for general cleaning. Do not use cleaners such as Pine Sol, Bleach or Swiffer Wet Jet. Steam mops should never be used on stained and sealed concrete as they may cause moisture to be trapped in the sealer and cause damage. Do not leave water to puddle on floor as this may cause white areas to form in your finish. In heavy traffic areas reapplication of wax may be required to maintain your glossy finish, after mopping and rinsing with your neutral cleaner, let dry completely and apply a thin coat of EZ FINISH.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

*This product is intended for use by trained professionals, experienced and trained in the use of these products. We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT.** We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may **CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET AND FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.***

COPYRIGHT 9/11/12 CPI